

K JOINT

Joint Compound



K JOINT

Easy Finish, Multi Purpose Joint Compound

General Information

- › Easy to mix and apply smoothly.
- › Flexible for non-cracking joints.
- › One product for both filling and finishing.
- › Controlled working time for work sequencing.
- › Mix 2 parts compound with 1 part clean water for maximum coverage area.

Knauf Joint Compound

Knauf Joint Compound is a gypsum based product designed for filling and finishing gypsum board joints and screw heads. It has an optimum working time for bedding in joints by hand and saves time.

Special Formula Jointing Compound

Specially formulated for use with gypsum boards all gypsum repair work and leveling the surface prior to applying paint or wall paper.

Product Information KNAUF Joint Compound

Mixing Ratio (Plaster : Water)	2:1
Working Time	45/60/90/120 minutes
Coverage Area	70 sq.m.
Shelf Life	9 months

Mixing Direction

Mix 2 parts compound to 1 part clean water. Mix together until consistently smooth with no lumps. Keep buckets and tools clean to avoid reduced working times.

Caution

Should not used in areas where temperature exceeds 45 degrees celcius or below zero degrees.

Storage

The bag should be tightly closed after use. Store above ground level in a dry place.



Mix Before use



Mixing Ratio



Setting Time
(45/60/90/120) minutes



Coverage Area



Shelf Life

GENERAL INFORMATION



Easy to mix



No cracks



Strong adhesion



Easy to sand



1 Use clean container and tools. Add water first then add compound in ratio of 1 water + 2 joint filler, mix it well for about 2-3 minutes. Mix both until consistently smooth with no lumps



2 Apply the first coat of compound by using 4" trowel to apply then, or putty knife in tape (paper or cotton). Fill any gaps (screw) at the joint and allow compound to set or dry about 45/60/90/120 minute's.



3 When the compound has set hard, apply the second coat and third coat with finishing trowel and allow each coat to set. When the final coat has dried, the joints and screw heads should be lightly sanded before painting.



KNAUF THAILAND



KNAUF OFFICE

Knauf Gypsum (Thailand) Limited
598 Q. House Ploenjit Building
9th, 18th – 19th Floor,
Room No. 9 CD, 18BC & 19B
Ploenjit Road, Lumpini,
Pathumwan Bangkok 10330
Thailand

> Tel: +66 (0) 2 6896077

> Fax: +66 (0) 2 6896001



KNAUF FACTORY

Knauf Gypsum (Thailand) Limited
Hemaraj Saraburi Industrial Estate
80 Moo 5, Nongplakradi Road,
Nongplamoh, Nongkhae
Saraburi 18140
Thailand

> Tel: +66 (0) 36 374526-8

> Fax: +66 (0) 36 374525



KNAUF DIGITAL

> Email : contact@knauf.co.th

> www.facebook.com/knauf.co.th

> www.knauf.co.th

Knauf Gypsum (Thailand) Limited
598 Q. House Ploenjit Building
9th, 18th – 19th Floor,
Room No. 9 CD, 18BC & 19B
Ploenjit Road, Lumpini,
Pathumwan Bangkok 10330
Thailand

Knauf Singapore
www.knauf.com.sg

Knauf Indonesia
www.knauf.co.id

Knauf Vietnam
www.knauf.com.vn

Knauf Philippines
www.knauf.com.ph